

# ABLOY® PROTEC<sup>2</sup>

TUBULAR DEADBOLTS





# ABLOY® PROTEC<sup>2</sup>



STANDARD BOLT  
ABLOY® LC801

DRIVE-IN BOLT  
ABLOY® LC802



A 2 3/8 (60 mm) or 2 3/4 (70 mm)  
(Adjustable)

A 2 3/8 (60 mm) or 2 3/4 (70 mm)  
(Adjustable)

## SECURITY FEATURES

- UL listed products
  - UL Burglary
  - UL 20 min fire rating
- Case hardened steel cylinder housing
- Rotating collar
- Optional key lockable thumbturn
- 6 mm steel retaining screws
- High security bolt
  - hardened steel with 2" length
  - 1" (25,4 mm) throw
- Reinforced steel strike box
- Protective bolt shield

CY411T  
DOUBLE CYLINDER

ME151  
c/LC801

ME152  
c/LC802



Bolt operated by key outside and inside.

## STANDARD FINISHES

CY412T  
SINGLE CYLINDER  
WITH THUMBTURN

ME153  
c/LC801

ME154  
c/LC802



Bolt operated by key outside and thumbturn inside.



US26/625  
Bright Chrome



US26D/626  
Satin Chrome



US3/605  
Bright Brass PVD



US4/606  
Satin Brass

CY413T  
SINGLE CYLINDER  
WITH KEY LOCKABLE  
THUMBTURN

ME155  
c/LC801

ME156  
c/LC802



Bolt operated by key outside and thumbturn inside.

Inside thumbturn can be locked with proper key to provide double cylinder security.

Fits 1 3/4" (44,5 mm) to 2 1/8" (54 mm) hole. Standard hardware for 1 3/4" (44,5 mm) thick door included.



www.abloy.com

Abloy Oy  
Wahlforssinkatu 20  
P.O.Box 108  
FI-80101 JOENSUU  
FINLAND  
Tel. +358 20 599 2501  
Fax +358 20 599 2209



An ASSA ABLOY Group brand

Abloy Oy is one of the leading manufacturers of locks, locking systems and architectural hardware and the world's leading developer of products in the field of electromechanical locking technology.

ASSA ABLOY is the global leader in door opening solutions, dedicated to satisfying end-user needs for security, safety and convenience.

ASSA ABLOY