




Cams

LEGEND



A Overall Dimension
(inches / mm)

B Center of Cam
to top of Cam
(inches / mm)



404837
Adams Rite MS
A .870 / 22.1
B .563 / 14.2



404838
Yale Standard
A 1.004 / 25.51
B .697 / 17.7



900006
Marks
A 1.083 / 27.51
B .776 / 19.71



900014
Russwin Cloverleaf
A 1.004 / 25.51
B .693 / 17.61



900038
Falcon
A 1.035 / 26.28
B .720 / 18.28



404839
Corbin Russwin
A 1.055 / 26.8
B .744 / 18.91



900045
**Corbin Russwin /
Schlage 9070**
exterior cam only
A 1.047 / 26.59
B .732 / 18.6



900039
Russwin / Segal
A 1.075 / 27.3
B .768 / 19.51



910006
Sargent / Yale
A 1.012 / 25.7
B .709 / 18.02




910005
Sargent Standard
A 1.00 / 25.3
B .697 / 17.71



900066
Schlage ME
A .913 / 23.18
B .598 / 15.19



900058
Adams Rite 4070
A .921 / 23.39
B .614 / 15.6



900067
Adams Rite / Lori
 A .850 / 21.59
 B .555 / 14.09



900055
Schlage A 9400
 A 1.009 / 25.6
 B .702 / 17.83



900056
Schlage L 9456/57/96
 A 1.008 / 25.6
 B .700 / 17.78




910001
BEST
 A 1.06 / 26.93
 B .735 / 18.68



900059
**Corbin /
 Emhart ML 2029**
 A 1.065 / 27.05
 B .745 / 18.93



900040
**Sargent
 8204, 05, 06, 8213**
 A 1.056 / 26.84
 B .771 / 19.59



404836
Schlage L 9456/57/96
 A .936 / 23.77
 B .644 / 16.35
*9050 older version
 9080 use with Abloy CY402,
 403, 415, 416, 5476, 5476
 9070 interior use only*



900072
**Schlage L
 9050/60/70/71**
newer version
 A .966 / 24.55
 B .688 / 17.47
interior and exterior

The above list is based on the information we have at time of printing, please check cam requirements and the dimensions before ordering, also check in the lock case for which it is to be used since many manufacturers dimensions and tolerances will change.