

1. ID code of the product type: Panic bar, surface mounted
2. Type number: PBE007
3. Intended use: For doors on escape routes
4. Manufacturer: Abloy Oy  
Joensuu factory  
Wahlforssinkatu 20  
FI-80100 Joensuu  
FINLAND
5. System or systems of assessment and verification of constancy of performance of the construction product: AVCP 1
6. Notified product certification body: VTT Expert Services Ltd  
ID No: 0809  
P.O. Box 1001  
FI-02044 VTT  
FINLAND

CE Certificates: No. 0809-CPR-1054

### 7. Declared performance:

Essential Characteristics	Grade	Performance	Harmonized technical specification
7.1 Category of use	3	High frequency of use where there is little intensive to exercise care	EN 1125:2008
7.2 Durability	7	200 000 test cycles	
7.3 Door mass	6	Up to 200 kg	
7.4 Suitability for use on fire/smoke doors	A	Suitable for use on smoke door assemblies	
7.5 Safety	1	All panic exit devices have a critical safety function	
7.6 Corrosion resistance	3	96 h (high resistance)	
7.7 Security	2	1000 N	
7.8 Projection of horizontal bar	1	Projection up to 150 mm (large projection)	
7.9 Type of horizontal bar operation	A	Panic exit device with "push-bar" operation	
7.10 Field door application	B	Single door only	
Dangerous substances	The materials used in the product do not contain or release any dangerous substances in excess of the maximum levels specified in existing European material standards or any national regulations.		

8. The performance of the product identified in points 1 and 2 is in conformity with the declared performance point 7. The declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Joensuu 2018-10-05  
On behalf of Abloy Oy

  
Jari Kervinen  
CTO