


- | | |
|---|--|
| 1. ID code of the product type: | Emergency exit device (lever handle) |
| 2. Type number: | EH060/030 (PRESTO 3-20 EXIT), EH070/030 (INOXI 3-19 EXIT), EH073/030 (INOXI 3-19k EXIT) , EH004/030 (FORUM EXIT), EH006/030 (POLAR 6 EXIT) |
| 3. Intended use: | For doors on escape routes |
| 4. Manufacturer: | Abloy Oy
Joensuu factory
Wahlforssinkatu 20
FI-80100 Joensuu
FINLAND |
| 5. System or systems of assessment and verification of constancy of performance of the construction product: | AVCP 1 |
| 6. Notified product certification body: | V Expert Services Ltd
ID No: 0809
P.O. Box 1001
FI-02044 VTT
FINLAND |
| CE Certificates: | No. 0809-CPR-1053 |

7. Declared performance:

Essential Characteristics	Grade	Performance	Harmonized technical specification
7.1 Category of use	3	High frequency of use where there is little intensive to exercise care	EN 179:2008
7.2 Durability	7	200 000 test cycles	
7.3 Door mass	6	Up to 200 kg	
7.4 Suitability for use on fire/smoke doors	B	Suitable for use on fire and smoke door assemblies based on a test in accordance with EN 1634-1.	
7.5 Safety	1	All emergency exit devices have a critical safety function	
7.6 Corrosion resistance	3	96 h (high resistance)	
7.7 Security	4	3 000 N	
7.8 Projection of operating element	2	Projection up to 100 mm (standard projection)	
7.9 Type of operation	A	Emergency exit device with "lever handle" operation	
7.10 Field of door application	B / C	Outwardly opening single exit door only / outwardly opening double exit door: inactive leaf only	
Dangerous substances	The materials used in the product do not contain or release any dangerous substances in excess of the maximum levels specified in existing European material standards or any national regulations.		

The performance of the product identified in points 1 and 2 is in conformity with the declared performance point 7. The declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Joensuu 2019-04-24
On behalf of Abloy Oy



Jari Kervinen
CTO