

## EU Declaration of performance (DoP)

No: DoP 24018-1

1. Product type: Emergency exit devices operated by a lever handle or push pad
  2. Type: EL418, EL419, MP418, EL515, EL518, EL519, MP515, MP518
  3. Intended use: For doors on escape routes
  4. Manufacturer: Abloy Oy  
Wahlforssinkatu 20  
80100 JOENSUU  
FINLAND
  5. System or systems of assessment and verification of constancy of performance of the construction product: AVCP 1
  6. Name and identification number of the notified body  
  
MPA NRW  
Materialprüfungsamt Nordrhein-Westfalen  
ID No: 0432  
Marsbruchstraße 186  
44287 Dortmund  
GERMANY
- CE Certificate: No. 0432-CPR-00008-01

### 7. Declared performance:

Harmonized technical specification EN 179:2008			
Essential Characteristics		Grade	Performance
7.1	Category of use	3	High frequency of use where there is little intensive to exercise care
7.2	Durability	7	200 000 test cycles
7.3	Door mass	6	Up to 200 kg door mass
7.4	Suitability for use on fire/smoke doors	0	Not suitable for use on fire door assemblies
7.5	Safety	1	All emergency exit devices have a critical safety function
7.6	Corrosion resistance	3	96 h (high resistance)
7.7	Security	4	3000 N
7.8	Projection of horizontal bar	2	Projection up to 100 mm (large projection)
7.9	Type of operation	A	Emergency exit device with "lever handle" operation
7.10	Field of door application	B/D	Outwardly opening single door only / Inwardly opening single door only
Dangerous substances		The materials used in the product do not contain or release any dangerous substances in excess of the maximum levels specified in existing European material standards or any national regulations.	

8. The performance of the product identified in points 1 and 2 is in conformity with the declared performance point 7. The declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

**Joensuu 2025-09-15**

Signed for and on behalf of Abloy Oy



Minna Sallinen  
VP & Head of product unit – ELMECH, DAS EMEIA

**Joensuu 2025-09-15**

Signed for and on behalf of Abloy Oy



Jari Kervinen  
Director and Head of Innovation, Mechanical Core PU  
Nordic



Abloy Oy lever handles according to the table below

EL418, EL419, MP418, EL515, EL518, EL519, MP515, MP518
ABLOY EH004 (FORUM 4)
ABLOY EH006 (POLAR 6)
ABLOY EH060 (PRESTO 3-20)
ABLOY EH070 (INOXI 3-19)
ABLOY EH073 (INOXI 3-19K)