

EU Declaration of performance (DoP)

No: 25076

1. Product type: Emergency exit devices operated by a lever handle or push pad
2. Type: LE945, LE955
3. Intended use: For doors on escape routes
4. Manufacturer: Abloy Oy
Wahlforssinkatu 20
80100 JOENSUU
FINLAND
AVCP 1
5. System or systems of assessment and verification of constancy of performance of the construction product:
6. Name and identification number of the notified body: MPA NRW
Materialprüfungsamt Nordrhein-Westfalen
ID No: 0432
Marsbruchstraße 186
44287 Dortmund
GERMANY
CE Certificate: No. 0432-CPR-00008-01
7. Declared performance:

Harmonized technical specification EN 179:2008			
Essential Characteristics		Grade	Performance
7.1	Category of use	3	High frequency of use where there is little intensive to exercise care
7.2	Durability	7	200 000 test cycles
7.3	Door mass	6	Up to 200 kg door mass
7.4	Suitability for use on fire/smoke doors	B / 0)	Suitable for use on fire door assemblies based on a test in accordance with EN 1634-1 / Not suitable for use on fire door assemblies based on a test in accordance with EN 1634-1
7.5	Safety	1	All emergency exit devices have a critical safety function
7.6	Corrosion resistance	3	96 h (high resistance)
7.7	Security	4	3000 N
7.8	Projection of operating element	2	Projection up to 100 mm (standard projection)
7.9	Type of operation	A	Emergency exit device with "lever handle" operation
7.10	Field of door application	A	Outwardly opening double exit door: passive leaf
Dangerous substances		The materials used in the product do not contain or release any dangerous substances in excess of the maximum levels specified in existing European material standards or any national regulations.	

*) Note, more details in installation instructions

8. The performance of the product identified in points 1 and 2 is in conformity with the declared performance point 7. The declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Joensuu 2025-09-15

Signed for and on behalf of Abloy Oy



Minna Sallinen
VP & Head of product unit – ELMECH, DAS EMEIA

Joensuu 2025-09-15

Signed for and on behalf of Abloy Oy



Jari Kervinen
Director and Head of Innovation, Mechanical Core PU
Nordic



Abloy Oy lever handles according to the table below

LE945, LE955
ABLOY EH060 (PRESTO 3-20)
ABLOY EH070 (INOXI 3-19)
ABLOY EH073 (INOXI 3-19k)
ABLOY EH004 (FORUM 4)
ABLOY EH006 (POLAR 6)