

## **EU Declaration of performance (DoP)**

No: 25093

L. Product type: Electric Lock

2. Type: MP520, MP522, MP524, EL566, EL567, EL568, EL569, MP564,

MP565

3. Intended use: Fire and smoke compartmentation doors

4. Manufacturer: Abloy Oy

Wahlforssinkatu 20 80100 JOENSUU

FINLAND

5. System or systems of assessment and verification of AVCP 1

constancy of performance of the construction product:

6. Name and identification number of the notified body Eurofins Expert Services Oy

ID No: 0809 Kivimiehentie 4 02150 ESPOO

CE Certificate: No. 0809-CPR-20002737

7. Declared performance:

Harmonized technical specification EN 14846:2008				
Essential Characteristics		Grade	Performance	
4.3	Category of use	3	Doors in public buildings	
4.4	Durability and load on latchbolt	S	200 000 test cycles, 50 N load on latchbolt	
4.5	Door mass and closing force	5	Up to 200 kg door mass, 25 N maximum closing force	
4.6	Suitability for use on fire/smoke doors	D	EI60 fire doors	
4.7	Safety	-	No safety requirement	
4.8	Corrosion resistance, temperature and humidity	L	High resistance, -25 °C to +70 °C, Level 2	
4.9	Security	6	Very high security, no drill resistance	
4.10	Security – Electrical function	1	Indication	
4.11	Security – Electrical manipulation	1	Grade	
Dangerous substances		substances	The materials used in the product do not contain or release any dangerous substances in excess of the maximum levels specified in existing European material standards or any national regulations.	



8.	The performance of the product identified in points 1 and 2 is in conformity with the declared performance point 7. The
	declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Joensuu 2025-11-12

Mmu Sali

Signed for and on behalf of Abloy Oy

Joensuu 2025-11-12

Signed for and on behalf of Abloy Oy

Minna Sallinen

VP & Head of product unit – ELMECH, DAS EMEIA

Jari Kervinen

Director and Head of Innovation, Mechanical Core PU

Nordic