1(2)

**ABLOY** 

## UKCA Declaration of performance No. 22020

Product type: Electric lock
Type number: EL582, EL754

3. Intended use: For use on fire doors when fitted in

accordance with the installation instructions

4. Manufacturer: Abloy Oy

Joensuu factory Wahlforssinkatu 20 FI-80100 JOENSUU

**FINLAND** 

5. System or systems of assessment and verification of constancy of performance

of the construction product: AVCP1

**6. Designated standard/s:**BS EN 14846:2008

7. Approved body: UL International (UK) LTD

ID No: 0843

Unit 1 - 3 Horizon, Kingsland Business Park,

Wade Road Basingstoke

Hampshire, RG24 8AH

**United Kingdom** 

8. UKCA Certificate/s of constancy of performance: No. 0843-CPR-1165



## 9. Declared performance:

Essential Characteristics	Grade	Performance	Designated technical specification
4.3 Category of use	3	Doors in public buildings	BS EN 14846:2008
4.4 Durability and load on latchbolt	S	200 000 test cycles, no load on latchbolt	
4.5 Door mass and closing force	5	Up to 200 kg door mass, 25 N maximum closing force	
4.6 Suitability for use on fire/smoke doors	F	EI120 fire doors	
4.7 Safety	-	See BS EN 179:2008, BS EN 1125:2008	
4.8 Corrosion resistance, temperature and humidity	L	High resistance, -25 °C to +70 °C, Level 2	
4.9 Security	3	Medium security, no drill resistance	
4.10 Security – Electrical function	1	Indication	
4.11 Security – Electrical manipulation	1	Grade 1	
Dangerous substances	The materials used in the product do not contain or release any dangerous substances in excess of the maximum levels specified in existing European material standards or any national regulations.		

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance point 9. The declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Joensuu 2022-09-16 On behalf of Abloy Oy

Jari Kervinen, VP Mechanical Solutions

Joensuu 2022-09-16 On behalf of Abloy Oy

Minna Sallinen, VP Digital Access Solutions