

## UKCA Declaration of performance No. 22023-1

- |   |   |
|---|---|
| <b>1. Product type:</b>   | Emergency exit devices operated by a lever handle   |
| <b>2. Type number:</b>  | <b>EL060, EL160, EL260, EL360, EL420,<br/>EL460, BL460, EL520, EL560, EL562,<br/>BL560, EL564, EL460L, EL560L</b>   |
| <b>3. Intended use:</b>   | For doors on escape routes when fitted in accordance with the installation instructions   |
| <b>4. Manufacturer:</b>   | Abloy Oy<br>Joensuu factory<br>Wahlforssinkatu 20<br>FI-80100 JOENSUU<br>FINLAND  |
| <b>5. System or systems of assessment and verification of constancy of performance of the construction product:</b> | AVCP 1  |
| <b>6. Designated standard/s:</b>  | BS EN 179:2008  |
| <b>7. Approved body:</b>  | UL International (UK) LTD<br>ID No: 0843<br>Unit 1 - 3 Horizon, Kingsland Business Park,<br>Wade Road<br>Basingstoke<br>Hampshire, RG24 8AH<br>United Kingdom |
| <b>8. UKCA Certificate/s of constancy of performance:</b>   | No. 0843-CPR-1173   |

## 9. Declared performance:

Essential Characteristics	Grade	Performance	Designated technical specification
7.1 Category of use	<b>3</b>	High frequency of use where there is little intensive to exercise care	<b>BS EN 179:2008</b>
7.2 Durability	<b>7</b>	200 000 test cycles	
7.3 Door mass	<b>6</b>	Up to 200 kg	
7.4 Suitability for use on fire/smoke doors	<b>0 / B *)</b>	Not approved for use on fire door assemblies / Suitable for use on fire door assemblies based on a test in accordance with BS EN 1634-1	
7.5 Safety	<b>1</b>	All emergency exit devices have a critical safety function	
7.6 Corrosion resistance	<b>3</b>	96 h (high resistance)	
7.7 Security	<b>4</b>	3 000 N	
7.8 Projection of operating element	<b>2</b>	Projection up to 100 mm (standard projection)	
7.9 Type of operation	<b>A</b>	Emergency exit device with "lever handle" operation	
7.10 Field of door application	<b>B/D</b>	Outwardly opening single exit door only/ Inwardly opening single exit door only	
<b>Dangerous substances</b>	The materials used in the product do not contain or release any dangerous substances in excess of the maximum levels specified in existing European material standards or any national regulations.		

\*) Note, more details in installation instructions

**10.** The performance of the product identified in points 1 and 2 is in conformity with the declared performance point 9. The declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Joensuu 2026-02-27  
On behalf of Abloy Oy



Minna Sallinen  
VP & Head of product unit – ELMECH, DAS EMEIA

Joensuu 2026-02-27  
On behalf of Abloy Oy



Jari Keränen  
Director and Head of Innovation, Mechanical Core PU  
Nordic