

## UKCA Declaration of performance No. 22024


- |  |   |
|--|---|
| 1. Product type:   | Panic exit devices operated by a horizontal bar   |
| 2. Type number:  | EL460, EL560, EL562, BL560, EL564,<br>EL460L, EL560L  |
| 3. Intended use:   | For doors on escape routes when fitted in accordance with the installation instructions   |
| 4. Manufacturer:   | Abloy Oy<br>Joensuu factory<br>Wahlforssinkatu 20<br>FI-80100 JOENSUU<br>FINLAND  |
| 5. System or systems of assessment and verification of constancy of performance of the construction product: | AVCP1   |
| 6. Designated standard/s:  | BS EN 1125:2008   |
| 7. Approved body:  | UL International (UK) LTD<br>ID No: 0843<br>Unit 1 – 3 Horizon, Kingsland Business Park,<br>Wade Road<br>Basingstoke<br>Hampshire, RG24 8AH<br>United Kingdom |
| 8. UKCA Certificate/s of constancy of performance:   | No. 0843-CPR-1174   |

## 9. Declared performance:

Essential Characteristics	Grade	Performance	Designated technical specification
7.1 Category of use	<b>3</b>	High frequency of use where there is little intensive to exercise care	<b>BS EN 1125:2008</b>
7.2 Durability	<b>7</b>	200 000 test cycles	
7.3 Door mass	<b>6</b>	Up to 200 kg	
7.4 Suitability for use on fire/smoke doors	<b>B</b>	Suitable for use on fire door assemblies based on a test in accordance with BS EN 1634-1	
7.5 Safety	<b>1</b>	All emergency exit devices have a critical safety function	
7.6 Corrosion resistance	<b>3</b>	96 h (high resistance)	
7.7 Security	<b>2</b>	1 000 N	
7.8 Projection of operating element	<b>1</b>	Projection up to 150 mm (large projection)	
7.9 Type of operation	<b>A</b>	Emergency exit device with "push-bar" operation	
7.10 Field of door application	<b>B</b>	Outwardly opening single exit door only	
<b>Dangerous substances</b>	The materials used in the product do not contain or release any dangerous substances in excess of the maximum levels specified in existing European material standards or any national regulations.		

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance point 9. The declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Joensuu 2022-11-24  
On behalf of Abloy Oy



Jari Kervinen, VP Mechanical Solutions

Joensuu 2022-11-24  
On behalf of Abloy Oy



Minna Sallinen, VP Digital Access Solutions