

## UKCA Declaration of performance No. 22038

- |   |   |
|---|---|
| <b>1. Product type:</b>   | Electric lock   |
| <b>2. Type number:</b>  | <b>EL432</b>  |
| <b>3. Intended use:</b>   | For use on fire doors when fitted in accordance with the installation instructions  |
| <b>4. Manufacturer:</b>   | Abloy Oy<br>Joensuu factory<br>Wahlforssinkatu 20<br>FI-80100 JOENSUU<br>FINLAND  |
| <b>5. System or systems of assessment and verification of constancy of performance of the construction product:</b> | AVCP1   |
| <b>6. Designated standard/s:</b>  | BS EN 14846:2008  |
| <b>7. Approved body:</b>  | UL International (UK) LTD<br>ID No: 0843<br>Unit 1 – 3 Horizon, Kingsland Business Park,<br>Wade Road<br>Basingstoke<br>Hampshire, RG24 8AH<br>United Kingdom |
| <b>8. UKCA Certificate/s of constancy of performance:</b>   | No. 0843-CPR-1172   |

## 9. Declared performance:

Essential Characteristics	Grade	Performance	Designated technical specification
4.3 Category of use	<b>3</b>	Doors in public buildings	<b>BS EN 14846:2008</b>
4.4 Durability and load on latchbolt	<b>S</b>	200 000 test cycles, no load on latchbolt	
4.5 Door mass and closing force	<b>2</b>	Up to 200 kg door mass, 50 N maximum closing force	
4.6 Suitability for use on fire/smoke doors	<b>C</b>	EI30 fire doors	
4.7 Safety	-	See BS EN 179:2008, BS EN 1125:2008	
4.8 Corrosion resistance, temperature and humidity	<b>L</b>	High resistance, -25 °C to +70 °C, Level 2	
4.9 Security	<b>6</b>	Very high security, no drill resistance	
4.10 Security – Electrical function	<b>1</b>	Indication	
4.11 Security – Electrical manipulation	<b>3</b>	Grade	
<b>Dangerous substances</b>	The materials used in the product do not contain or release any dangerous substances in excess of the maximum levels specified in existing European material standards or any national regulations.		

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance point 9. The declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Joensuu 2026-02-27  
On behalf of Abloy Oy



Minna Sallinen  
VP & Head of product unit – ELMECH, DAS EMEIA

Joensuu 2026-02-27  
On behalf of Abloy Oy



Jari Kervinen  
Director and Head of Innovation, Mechanical Core PU Nordic