1(2)

ABLOY

UKCA Declaration of performance No. 22032

Product type: Single-axis hinge
Type number: 110x36KSS-F

3. Intended use: On fire compartmentation doors

4. Manufacturer: Abloy Oy

Joensuu factory Wahlforssinkatu 20 FI-80100 JOENSUU

FINLAND

5. System or systems of assessment and verification of constancy of performance

of the construction product: AVCP1

6. Designated standard/s: BS EN 1935:2002/AC:2003

7. Approved body: UL International (UK) LTD

ID No: 0843

Unit 1 - 3 Horizon, Kingsland Business Park,

Wade Road Basingstoke

Hampshire, RG248AH

United Kingdom

8. UKCA Certificate/s of constancy of performance: No. 0843-CPR-1185



9. Declared performance:

Essential Characteristics	Grade	Performance	Designated technical specification
4.2 Category of use	4	Severe duty, doors which are subject to fre-	
		quent violent use	
4.3 Durability	7	200 000 cycles	
4.4 Test door mass	5	100 kg	
4.5 Suitability for use on fire/smoke compartmentation	1	Suitable for use on fire compartmentation	BS EN 1935:2002/
doors		doors	AC:2003
4.6 Safety	1	Only grade 1 identified	
4.7 Corrosion resistance	3	High corrosion resistance	
4.8 Security - Burglar-resistance	1	Suitable for use on burglar-resistant doors	
4.9 Hinge grade	12	Grade 12	
Dangerous substances	The materials used in the product do not contain or release		
	any dangerous substances in excess of the maximum lev-		
	els specified in existing European material standards or		
	any national regulations.		

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance point 9. The declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Joensuu 2022-09-21 On behalf of Abloy Oy

Jari Kervinen, VP Mechanical Solutions

Joensuu 2022-09-21 On behalf of Abloy Oy

Minna Sallinen, VP Digital Access Solutions