

UKCA Declaration of performance No. 22012


- | | |
|--|---|
| 1. Product type: | Mechanically operated lock |
| 2. Type number: | LC194 |
| 3. Intended use: | On fire compartmentation doors |
| 4. Manufacturer: | Abloy Oy
Joensuu factory
Wahlforssinkatu 20
FI-80100 JOENSUU
FINLAND |
| 5. System or systems of assessment and verification of constancy of performance of the construction product: | AVCP 1 |
| 6. Designated standard/s: | BS EN 12209:2003 / BS EN 12209/AC:2005 |
| 7. Approved body: | UL International (UK) LTD
ID No: 0843
Unit 1 – 3 Horizon, Kingsland Business Park,
Wade Road
Basingstoke
Hampshire, RG24 8AH
United Kingdom |
| 8. UKCA Certificate/s of constancy of performance: | No. 0843-CPR-1170 |

9. Declared performance:

Essential Characteristics	Grade	Performance	Designated technical specification
4.2.1 Category of use	3	For use in doors where there is a high chance of misuse	BS EN 12209:2003 BS EN 12209/AC:2005
4.2.2 Durability and load on latch bolt	X	200 000 test cycles, 120 N load on latch bolt	
4.2.3 Door mass and closing force	5	200kg and 25N closing force	
4.2.4 Suitability for use on fire/smoke doors	1	Suitable for use on fire/smoke resisting door assemblies	
4.2.5 Safety	0	No safety requirement	
4.2.6 Corrosion resistance and temperature	F	High corrosion resistance, temperature range from -20 °C to +80 °C	
4.2.7 Security and drill resistance	3	Medium security and no drill resistance	
4.2.8 Field of door application	B	Mortice, hinged door	
4.2.9 Type of key operation and locking	B	Cylinder lock, automatically locking	
4.2.10 Type of spindle operation	0	Lock without follower	
4.2.11 Key identification	0	No requirements	
Dangerous substances	The materials used in the product do not contain or release any dangerous substances in excess of the maximum levels specified in existing European material standards or any national regulations.		

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance point 9. The declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Joensuu 2022-09-14
On behalf of Abloy Oy



Jari Kervinen, VP Mechanical Solutions

Joensuu 2022-09-14
On behalf of Abloy Oy



Minna Sallinen, VP Digital Access Solutions